



Heavy Duty & Mixed Fleet

NITRITE FREE

EXTENDED LIFE COOLANT



Learn More about our technology on the back

**Cummins® Certified - CES 14636
CES 14439**

Detroit Diesel® Certified - 93K217

See all OEM listings below

✓ **Protects Against Rust & Corrosion**

✓ **1,200,000 km Fluid Guarantee***

When extender added at 960,000 km

✓ **For use in:**

- Heavy & Light Duty Vehicles - Classes 1-8
- Aluminum & Cast Iron Components
- Diesel Engines & Natural Gas Engines

Meets or Exceeds OEM Performance Requirements:

Cummins CES 14636/14439	CAT EC-1
Detroit Diesel 93K217	Freightliner
Navistar CEMS B-1, Type IIIA	Paccar
International	Paccar CS 0185
Volvo	Peterbilt
Mack	Kenworth
John Deere H24	GM 6277M
John Deere H24 C1	GMW 34290
John Deere JDS-G135	Ford WSS-M97-B44D

Meets or Exceeds Industry & Governmental Standards:

ASTM D6210	ASTM D7583	TMC RP364	SAE J1034
ASTM D3306	ASTM D4340	TMC RP351	SAE J1941
ASTM D4985	TMC RP338A	JIS K2234	

*To achieve service life: (1) Perform cooling system flush, then fill with proper mixture of Nitrite Free ELC (NF-ELC) Concentrate and high quality water. (2) Top off with NF-ELC Prediluted coolant as necessary. (3) Test coolant using refractometer and test strips to assess pH and nitrite contamination. (4) Add NF-ELC Prediluted or Nitrite Free-OAT coolant extender in accordance with OEM recommendations at, or 960,000 km to maintain pH and inhibitor levels. (5) Use new coolant if replacing a cooling system part. Additional terms and conditions apply – Prestone.com or 1-888-269-0750 for information. PRESTONE COMMAND® is a registered trademark of Prestone Products Corporation. All other marks are those of their respective owners.



Heavy Duty & Mixed Fleet

NITRITE FREE

EXTENDED LIFE COOLANT

CONCENTRATE	PACK	UPC
74089	6/3.78 L	6 20235-74089 4
74807	205 L drum	6 20235-74807 4
74347-1KL	1000 L tote	6 20235-74347 5

READY TO USE	PACK	UPC
74097	6/3.78 L	6 20235-74097 9
74815	205 L drum	6 20235-74815 9
74352-1KL	1000 L tote	6 20235-74352 9

74089 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	96.7%
Total Water:	3.3%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Yellow	
Odor:	Characteristic	
Ash Content:	1.9% by weight	ASTM D1119
pH at 50 vol%:	8.2-8.8	ASTM D1287
Reserve Alkalinity:	4.4 mL	ASTM D1121
Density at 15°C, g/mL:	1.1159	ASTM D1122
Freezing Point at 50 vol%:	-34°F (-37°C)	ASTM D1177
Boiling Point at 50 vol%: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	53 mL/1.5 sec.	ASTM D1881

74097 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	52.4%
Total Water:	47.6%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Yellow	
Odor:	Characteristic	
Ash Content:	0.75% by weight	ASTM D1119
pH:	8.2-8.8	ASTM D1287
Reserve Alkalinity:	2.2 mL	ASTM D1121
Density at 15°C, g/mL:	1.0734	ASTM D1122
Freezing Point:	-34°F (-37°C)	ASTM D1177
Boiling Point: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	53 mL/1.5 sec.	ASTM D1881

Most of our COMMAND® Antifreeze+Coolant Products come in 205 L Drums and 1000 L Totes.



205 L drum

1,000 L tote