



Heavy Duty EXTENDED SERVICE INTERVAL SCA PRE-CHARGED



Learn More about our technology on the back

Detroit Diesel® Certified - 93K217

See all OEM listings below

✓ **Protects Against Rust & Corrosion**

✓ **Low Silicate Formula**

✓ **No Phosphates**

✓ **For use in:**

- Heavy & Medium Duty Vehicles - Classes 6-8
- Aluminum & Cast Iron Components
- Diesel Engines & Natural Gas Engines

Meets or Exceeds OEM Performance Requirements:

Cummins CES 14439	Navistar CEMS B-1, Type II
Cummins CES 90T8-4	Freightliner 48-22880
Detroit Diesel 93K217	Kenworth R026-170-97
Detroit Diesel 7SE298	Peterbilt 8502.002
Mack 014617004	John Deere H24, H24 A1
Freightliner 48-25961	John Deere JDS-G135
Freightliner 48-25878	John Deere 8650-5

Meets or Exceeds Industry & Governmental Standards:

ASTM D6210	ASTM D4340	TMC RP329A	SAE J1034
ASTM D3306	GCA A-A-52624	TMC RP338A	SAE J1941
ASTM D4985	CID A-A-52624A	TMC RP351	



Heavy Duty EXTENDED SERVICE INTERVAL SCA PRE-CHARGED

CONCENTRATE	PACK	UPC	READY TO USE	PACK	UPC
74005	6/3.78 L	6 20235-74005 4	74013	6/3.78 L	6 20235-74013 9
74021	205 L drum	6 20235-74021 4	74039	205 L drum	6 20235-74039 9
74305-1KL	1,000 L tote	6 20235-74305 5	74313-1KL	1,000 L tote	6 20235-74313 0

74005 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	96.8%
Total Water:	3.2%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.50% by weight	Federal #209B
pH at 50 vol%:	10.9	ASTM D1287
Reserve Alkalinity:	5.7 mL	ASTM D1121
Density at 15°C, g/mL:	1.1189	ASTM D1122
Freezing Point at 50 vol%:	-34°F (-37°C)	ASTM D1177
Boiling Point at 50 vol%: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	20 mL/0.6 sec.	ASTM D1881

74013 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	52.3%
Total Water:	47.7%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.34% by weight	Federal #209B
pH:	10.9	ASTM D1287
Reserve Alkalinity:	2.8 mL	ASTM D1121
Density at 15°C, g/mL:	1.0724	ASTM D1122
Freezing Point:	-34°F (-37°C)	ASTM D1177
Boiling Point: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	20 mL/0.6 sec.	ASTM D1881

Most of our COMMAND® Antifreeze+Coolant Products come in 205 L Drums and 1000 L Totes.



205 L drum

1,000 L tote